Printing date 10/07/2016

Reviewed on 10/07/2016

### 1 Identification

- · Product identifier
- · Trade name: KMS Therma Shape Shaping Blow Dry
- · Article number: 132169 25ml / 132170 200ml
- · Application of the substance / the mixture Hair Cosmetics
- · Manufacturer/Supplier:

Kao USA Inc.

2535 Spring Grove Avenue Cincinnati, Ohio 45214 / USA KaoGermanySDS @kao.com

- · Information department: CHEMTREC
- Emergency telephone number: CHEMTREC (US): (800)424-9300

CHEMTREC (Outside US): +1 (703) 527-3887 (24h)

### 2 Hazard(s) identification

· Classification of the substance or mixture

Flam. Lig. 3 H226 Flammable liquid and vapor.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · Hazard pictograms





GHS02 GHS07

- · Signal word Warning
- · Hazard-determining components of labeling:

Fragrance

Benzophenone-4

· Hazard statements

H226 Flammable liquid and vapor.

H317 May cause an allergic skin reaction.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P233 Keep container tightly closed.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.

P302+P352 IF ON SKIN: Wash with plenty of water. P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 0 Fire = 2 Reactivity = 0

(Contd. on page 2)

Printing date 10/07/2016

Trade name: KMS Therma Shape Shaping Blow Dry

(Contd. of page 1)

Reviewed on 10/07/2016

· HMIS-ratings (scale 0 - 4)



Health = 0 Fire = 2 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

# 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 64-17-5	ethanol	2.5-<10%
	♦ Flam. Liq. 2, H225	
	Fragrance	0.2-0.7%
	♦ Skin Sens. 1, H317 Flam. Liq. 4, H227	
CAS: 4065-45-6	Benzophenone-4	0.2-0.7%
	♦ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1B, H317	

#### 4 First-aid measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor: Treat symptomatically.
- Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

No further relevant information available.

- · Advice for firefighters
- · Protective equipment: No special measures required.

. 1 10

Printing date 10/07/2016 Reviewed on 10/07/2016

Trade name: KMS Therma Shape Shaping Blow Dry

(Contd. of page 2)

# 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

	Ψ		
CAS:	CAS: 64-17-5 ethanol (2.5-<10%)		
PEL	Long-term value: 1900 mg/m³, 1000 ppm		
REL	Long-term value: 1900 mg/m³, 1000 ppm		
TLV	Short-term value: 1880 mg/m³, 1000 ppm		
Propy	Propylene Glycol (0.1- <u>&lt;</u> 2.%)		
WEEL	WEEL Long-term value: 10 mg/m³		

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 4)

(Contd. of page 3)

# Safety Data Sheet acc. to OSHA HCS

Printing date 10/07/2016 Reviewed on 10/07/2016

Trade name: KMS Therma Shape Shaping Blow Dry

#### · Protection of hands:



Not required under normal conditions. The details concerned are recommendations. The glove material has to be impermeable and resistant to the product / the substance / the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation. - Please contact the glove supplier for futher information.

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Not required under normal conditions If there is a risk of splashing: safety glasses

### 9 Physical and chemical properties

· Information on basic physical and o	chemical properties	
· General Information		
· Appearance:	125.24	
Form:	Liquid	
Color: · Odor:	Yellow Aromatic	
· Odor: · Odor threshold:	Not determined.	
· pH-value at 20 °C (68 °F):	5.6	
· Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	Undetermined.	
· Flash point:	55 °C (131 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.	
· Vapor pressure at 20 °C (68 °F):	23 hPa (17 mm Hg)	
· Density at 20 °C (68 °F):	1.0035 g/cm³ (8.374 lbs/gal)	
· Relative density `	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/water): Not determined.		

(Contd. on page 5)

Printing date 10/07/2016 Reviewed on 10/07/2016

Trade name: KMS Therma Shape Shaping Blow Dry

		(Contd. of page 4
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	6.0 %	
Water:	87.5 %	
VOC content:	6.0 %	
Solids content:	2.8 %	
· Other information	her information No further relevant information available.	

# 10 Stability and reactivity

- · Reactivity No dangerous reactions known if used as directed.
- · Chemical stability The product is stable under standard conditions.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

# 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
CAS: 64-17-5	ethanol	1

### · NTP (National Toxicology Program)

None of the ingredients is listed.

#### · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

# 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

(Contd. on page 6)

(Contd. of page 5)

# Safety Data Sheet acc. to OSHA HCS

Printing date 10/07/2016 Reviewed on 10/07/2016

Trade name: KMS Therma Shape Shaping Blow Dry

· Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

# 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

4 4 -			2.0
7/1	ranspor	t intorr	nation
17 1	Ialiopul	LIIIIQII	паичн

· UN-Number	
· DOT, IMDG, IATA	UN1993

· UN proper shipping name

· DOT Flammable liquids, n.o.s. (Ethanol)

FLAMMABLE LIQUID, N.O.S. (ETHANOL) · IMDG, IATA

- · Transport hazard class(es)
- · DOT



· Class 3 Flammable liquids

· Label

· IMDG, IATA



· Class 3 Flammable liquids

· Label

· Packing group

DOT, IMDG, IATA III

· Environmental hazards: Not applicable.

· Special precautions for user Warning: Flammable liquids

Danger code (Kemler): 30 · EMS Number: F-E,S-E · Stowage Category Α

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

(Contd. on page 7)

Printing date 10/07/2016 Reviewed on 10/07/2016

Trade name: KMS Therma Shape Shaping Blow Dry

(Contd. of page 6)

· Transport/Additional information:

· DOT

• **Quantity limitations**On passenger aircraft/rail: 60 L
On cargo aircraft only: 220 L

· IMDG

Limited quantities (LQ)
 Excepted quantities (EQ)
 Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation": UN 1993 FLAMMABLE LIQUIDS, N.O.S.

(ETHANOL), 3, III

# 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

CAS: 122-99-6 2-Phenoxyethanol

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

CAS: 64-17-5 ethanol

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

CAS: 64-17-5 ethanol

А3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapor.

H227 Combustible liquid.

(Contd. on page 8)

Printing date 10/07/2016

Reviewed on 10/07/2016

Trade name: KMS Therma Shape Shaping Blow Dry

(Contd. of page 7)

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

- · Department issuing SDS: Regulatory Affairs
- Date of preparation / last revision 10/07/2016 / 3
- · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Flam. Liq. 4: Flammable liquids – Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation - Category 1B

· \* Data compared to the previous version altered.