

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/04/2022

Reviewed on 11/04/2022

1 Identification

- **Product identifier**
- **Trade name:** KMS HAIR STAY Anti-Humidity Seal [75ml; 150ml]
- **Article number / Bulk number** 142024; 142025
- **Product category** PC39 Cosmetics, personal care products
- **Application of the substance / the mixture** Hair cosmetics
- **Manufacturer/Supplier:**
Kao USA Inc.
2535 Spring Grove Avenue
Cincinnati, Ohio 45214 / USA
KaoGermanySDS@kao.com
- **Information department:** CHEMTREC
- **Emergency telephone number:**
CHEMTREC (US): (0800) 424-9300
CHEMTREC (Outside US): +1 (703) 527-3887 (24h)

2 Hazard(s) identification

- **Classification of the substance or mixture**

Flammable Aerosols 1	H222 Extremely flammable aerosol.
Gases under Pressure - Compressed gas	H280 Contains gas under pressure; may explode if heated.
Specific Target Organ Toxicity - Single Exposure 3	H336 May cause drowsiness or dizziness.
Aspiration Hazard 1	H304 May be fatal if swallowed and enters airways.

- **Label elements**
- **Hazard pictograms**



GHS02 GHS04 GHS07 GHS08

- **Signal word** Danger
- **Hazard-determining components of labeling:**
Pentane
Isopropanol
dipentene
- **Hazard statements**
H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H336 May cause drowsiness or dizziness.
H304 May be fatal if swallowed and enters airways.
- **Precautionary statements**
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P271 Use only outdoors or in a well-ventilated area.
P301+P310 If swallowed: Immediately call a poison center/doctor.

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/04/2022

Reviewed on 11/04/2022

Trade name: KMS HAIR STAY Anti-Humidity Seal [75ml; 150ml]

(Contd. of page 1)

- P331 Do NOT induce vomiting.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P312 Call a poison center/doctor if you feel unwell.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.
 P410+P403 Protect from sunlight. Store in a well-ventilated place.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



- **Other hazards**
 · **Results of PBT and vPvB assessment**
 · **PBT:** Not applicable.
 · **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
 · **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 64-17-5	Ethanol ⚠ Flammable Liquids 2, H225	25-30%
CAS: 109-66-0	Pentane ⚠ Flammable Liquids 2, H225 ⚠ Aspiration Hazard 1, H304 ⚠ Specific Target Organ Toxicity - Single Exposure 3, H336	≥15-<20%
CAS: 107-51-7	Octamethyltrisiloxane ⚠ Flammable Liquids 3, H226	15-20%
CAS: 67-63-0	Isopropanol ⚠ Flammable Liquids 2, H225 ⚠ Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336	≤2.5%
CAS: 70131-69-0	Phenyl Trimethicone ⚠ Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 3, H311; Acute Toxicity - Inhalation 2, H330	≤2.5%

4 First-aid measures

- **Description of first aid measures**
 · **General information:** No special measures required.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/04/2022

Reviewed on 11/04/2022

Trade name: KMS HAIR STAY Anti-Humidity Seal [75ml; 150ml]

(Contd. of page 2)

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**
Immediately rinse with water.
Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:** Treat symptomatically.
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
Vapors can form a highly flammable mixture with air
- **Advice for firefighters**
- **Protective equipment:**
Mouth respiratory protective device.
Do not inhale explosion gases or combustion gases.
Wear fully protective suit.
- **Additional information**
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
Collect contaminated fire fighting water separately. It must not enter the sewage system.
Highly flammable. Vapours are heavier than air and may spread along floors. Vapours or gases may travel considerable distances to ignition source and flash back.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to penetrate the ground/soil.
- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:**
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

(Contd. on page 4)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/04/2022

Reviewed on 11/04/2022

Trade name: KMS HAIR STAY Anti-Humidity Seal [75ml; 150ml]

(Contd. of page 3)

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store only in the original receptacle.
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

CAS: 64-17-5 Ethanol

TLV	Short-term value: 1000 ppm A3
-----	----------------------------------

CAS: 109-66-0 Pentane

TLV	Long-term value: 1000 ppm
-----	---------------------------

CAS: 67-63-0 Isopropanol

PEL	Long-term value: 980 mg/m ³ , 400 ppm
REL	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV	Short-term value: 400 ppm Long-term value: 200 ppm BEI, A4

- **Ingredients with biological limit values:**

CAS: 67-63-0 Isopropanol

BEI	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
-----	---

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes.
- **Breathing equipment:** Not required.
- **Protection of hands:**



Protective gloves

(Contd. on page 5)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/04/2022

Reviewed on 11/04/2022

Trade name: KMS HAIR STAY Anti-Humidity Seal [75ml; 150ml]

(Contd. of page 4)

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Goggles recommended during refilling.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Aerosol
Color:	Colorless
Odor:	Characteristic
Odor threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Not applicable, as aerosol.

· **Flash point:** Not applicable, as aerosol.

· **Flammability (solid, gaseous):** Not applicable.

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Vapor pressure at 20 °C (68 °F):** 5,100 hPa (3.800 mm Hg)

· **Density at 20 °C (68 °F):** 0.8185 g/cm³ (6.83038 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not applicable.

· **Solubility in / Miscibility with**

Water: Fully miscible.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

Dynamic: Not determined.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/04/2022

Reviewed on 11/04/2022

Trade name: KMS HAIR STAY Anti-Humidity Seal [75ml; 150ml]

(Contd. of page 5)

Kinematic:	Not determined.
Solvent content:	
Organic solvents:	48.6 %
Water:	0.0 %
VOC content:	48.61 %
Solids content:	17.5 %
Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity**

No dangerous reactions known if used as directed.

No further relevant information available.

- **Chemical stability** The product is stable under standard conditions.

- **Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

- **Possibility of hazardous reactions** No dangerous reactions known.

- **Conditions to avoid** No further relevant information available.

- **Incompatible materials:** No further relevant information available.

- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

CAS: 75-37-6 Hydrofluorocarbon 152a

Inhalative LC50/4 h 977 mg/l (mouse)

- **Primary irritant effect:**

- **on the skin:** No irritant effect.

- **on the eye:** No irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

CAS: 64-17-5 Ethanol	1
CAS: 67-63-0 Isopropanol	3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/04/2022

Reviewed on 11/04/2022

Trade name: KMS HAIR STAY Anti-Humidity Seal [75ml; 150ml]

(Contd. of page 6)

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.


12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Smaller quantities can be disposed of with household waste.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- | | |
|--|---------------------|
| <ul style="list-style-type: none"> · UN-Number | UN1950 |
| <ul style="list-style-type: none"> · DOT, ADR/RID/ADN, IMDG, IATA | UN1950 |
| <ul style="list-style-type: none"> · UN proper shipping name | Aerosols, flammable |
| <ul style="list-style-type: none"> · DOT | AEROSOLS |
| <ul style="list-style-type: none"> · IMDG | AEROSOLS |
| <ul style="list-style-type: none"> · IATA | AEROSOLS, flammable |
| <ul style="list-style-type: none"> · Transport hazard class(es) | |
| <ul style="list-style-type: none"> · DOT | |
| <div style="text-align: center;">  </div> | |
| <ul style="list-style-type: none"> · Class | 2.1 Gases |

(Contd. on page 8)

US

Safety Data Sheet



acc. to OSHA HCS

Printing date 11/04/2022

Reviewed on 11/04/2022

Trade name: KMS HAIR STAY Anti-Humidity Seal [75ml; 150ml]

(Contd. of page 7)

· Label	2.1
· ADR/RID/ADN	
	
· Class	2.5F Gases
· Label	2.1
· IMDG, IATA	
	
· Class	2.1 Gases
· Label	2.1
· Packing group	
· DOT, ADR/RID/ADN, IMDG, IATA	Void
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Gases
· Hazard identification number (Kemler code):	-
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg
· ADR/RID/ADN	
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity

(Contd. on page 9)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/04/2022

Reviewed on 11/04/2022

Trade name: KMS HAIR STAY Anti-Humidity Seal [75ml; 150ml]

(Contd. of page 8)

· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.

- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

CAS: 67-63-0 | Isopropanol

CAS: 75-65-0 | t-Butyl Alcohol

- **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

- **Hazardous Air Pollutants**

None of the ingredients is listed.

- **Chemicals known to cause cancer:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

CAS: 64-17-5 | Ethanol

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

- **TLV (Threshold Limit Value)**

CAS: 64-17-5 | Ethanol

A3

CAS: 67-63-0 | Isopropanol

A4

CAS: 75-65-0 | t-Butyl Alcohol

A4

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/04/2022

Reviewed on 11/04/2022

Trade name: KMS HAIR STAY Anti-Humidity Seal [75ml; 150ml]

(Contd. of page 9)

· **Relevant phrases**

H225 Highly flammable liquid and vapor.
 H226 Flammable liquid and vapor.
 H301 Toxic if swallowed.
 H304 May be fatal if swallowed and enters airways.
 H311 Toxic in contact with skin.
 H319 Causes serious eye irritation.
 H330 Fatal if inhaled.
 H336 May cause drowsiness or dizziness.

· **Department issuing SDS:** Regulatory Affairs

· **Date of preparation / last revision** 11/04/2022

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Aerosols 1: Aerosols – Category 1

Gases under Pressure - Compressed gas: Gases under pressure – Compressed gas

Flammable Liquids 2: Flammable liquids – Category 2

Flammable Liquids 3: Flammable liquids – Category 3

Acute Toxicity - Oral 3: Acute toxicity – Category 3

Acute Toxicity - Inhalation 2: Acute toxicity – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

Aspiration Hazard 1: Aspiration hazard – Category 1

US